

*Chassis*

*Year:* 2016

*Make:* Kenworth

*Model:* T880

*Odometer:* New

*Engine Type:* Paccar MX 455hp @ 1700 RPM; 1650 ft/lb torque @ 1000 RPM

*Truck G.V.W:* 60,000# w/ 13,500# Pusher axle (11,020# tire limited)

*Transmission:* Eaton Fuller Ultra-Shift Plus

*Rear End Type:* Twin Screw w/ lift axle

*Rear Axle:* 40,000#

*R Suspension:* Neway ADZ246 46K w/ 13,500# Watson-Chalin steerable pusher axle

*Front Axle:* 20,000#

*F Suspension:* Taper Leaf

*Front Tires:* Bridgestone M854 385/65R22.5 18PR

*Rear Tires:* Bridgestone M799 11R22.5 16PR

*Wheels:* Alcoa aluminum

*Brake type:* Air brakes

***Tank***

***Year:*** 2015

***Make:*** Almac

***Model:*** LP45A

***D.O.T. Code:*** DOT-406-AL

***Compartments:*** 5

***Capacity:*** 4,500 Gallons

***Compartment Sizes:*** 1000-1000-1000-1000-500

***Bulkheads:*** All double

***Pumps:*** Dual 2.5" Blackmer w/ Air bypass curbside

***PTO Controls:*** Seneca Pro-Air Panel: Panel installed across rear door opening with emergency valve and PTO controls.

Auto off with brake release. High/low flow control. Trucknology product indicators.

***Meters:*** Curbside: LCR600, 2" 150GPM Hi-Cap w/ Seneca Pro-Air Preset; Streetside: LCR600, 2" 100GPM

w/electronic preset. Both meters facing rear. Dual printers in cab.

***Spit Tanks:*** Dual Aluminum

***Hose Reels:*** Dual Hanney Electric Inverted. Side dispensing with heavy duty 2" stainless roller assemblies. Center Hose

Reel - Rear facing. 3-way diverter valve installed between the curbside meter and curb side hose reel.

***Delivery Hoses:*** Curbside 1-3/8" x 125', Streetside 1-3/8" x 50', Center 2"x40' hose

***Nozzles:*** Dual 1.5" EBW Manual nozzles. Center: 2" Scully nozzle w/ interchangeable 2" & 1.5" spouts

***Manifold:*** 3" Civacon dual bank air operated manifold installed in the curbside cabinet. Seneca Tank Pro-Air Panel

Controls. (1) butterfly valve with 3" male adapter, dust cap, and sight glass installed on each bank of manifold for gravity drop

***Bottom Load:*** Yes, Openable API's. Rack Ready

***V-K:*** New

***I-P:*** New