

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
1	Dual Wheel Truck Heavy Duty Tools Dolly	OTC1770A	OTC or Equivalent. Hydraulic jack provides almost 5" of lift and tilts wheel assembly 4° to prevent damage to wheel seal. Swivel casters for easy maneuverability. 6' chain holds load in place.	4		
2	Portable Generator 2ZRP7	2ZRP7	Dayton Portable Generator or Equivalent, 3500 Rated Watts, 6380 Surge Watts, 120/240 Voltage, Circuit Breaker Protected, Engine Size 242cc, Run Time @ Full Load 9.3 Hr/Tank, Sound Level dB 75.7, Engine HP 8, Fuel Tank Capacity 5.7 Gal, Starter Type Recoil, Air Cleaner Type Foam Element, Low Oil Shut Down, Engine Brand Honda, Includes Wheel Kit.	5		
3	Tongue and Groove Plier, 10 1/4 In L.	1UKH8	Westward Tongue and Groove Plier or Equivalent. Overall Length 10 1/4 In, Max Jaw Opening 1 1/4 In, Jaw Length 3/8 In, Number of Positions 6, Grooved Joint Adjustment, Slip Resistant Dipped Grip Handle, Tempered Steel Construction, Nickel Plated Finish, Multiple Positions, Adjustable, Angled Teeth, More Points Of Contact For Improved Grip, Slightly Curved Gripping.	7		
4	Hex Key Set	1FX36	Measurement Type Metric, Arm Type Short, Number of Pieces 15, Arm Length 1.20 to 6.10 In., Sizes Included 0.7, 0.9, 1.3, 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10, 12, 14, 17mm, Blade Material Heat Treated Alloy Steel, Black Oxide Finish, Handle Type L-Shaped, Meets/Exceeds Federal Specification GGG - K275D, Includes Metal Box Country of Origin (Country of Origin is subject to change.)USA Item:Hex Key Set Measurement Type:Metric Arm Type:Short Handle Type:L-Shaped Number of Pieces:15 Arm Length:1.20 to 6.10" Sizes Included:0.7, 0.9, 1.3, 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10, 12, 14, 17mm Blade Material:Heat Treated Alloy Steel Finish:Black Oxide Meets/Exceeds:Federal Specification GGG - K275D	4		

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
5	Plier Tongue/Groove	264SG	Proto or Equivalent. Straight Jaw Type Length 12 In Max Jaw Opening 2 5/8 In Plastic Cushion Grip Handle Natural Finish Material Tool Steel For Use With Rods Pipes And Cable Connections	5		
6	Corded 3/8" Pro Rear Handle Drill	28126	Craftsman or Equivalent. 6.5 Amp motor provides the torque, power and durability for continuous drilling and screwdriving. Variable speed 0-2500 rpm allows matching of speeds to a variety of materials in a wide range of high-torque job applications. The trigger switch with lock-on button controls variable speeds and provides comfortable one hand control. The 3/8 in. keyless chuck hand tightens bits quickly and securely without a chuck key. An ergonomically designed rear handle provides a positive grip, balance and comfort. A built-in level is top mounted for accurate horizontal and vertical drilling and screwdriving.	15		
7	Torque Wrench 3/4 Dr	6017B	Proto or Equivalent. Drive size: 3/4, Head type: fixed, Primary scale range: 120 to 600 Ft.-Lbs., Primary scale increments: 2.0 Ft.- Lbs., Overall length: 41-3/16, Weight: 8.80.	5		
8	Fixed Head Micrometer Torque Wrench	J6013C	Proto or Equivalent. Product Details: Length 26",678.66mm , Weight 5.9 lbs, 2.68 kilos, Drive Size 1/2", Head Depth 1-7/32", Head Length 1-1/8" , Increments (ft/lb) 1 ft. lb., Torque Range (ft/lb) 50 – 250.	3		
9	Flexible Magnetic Retrieving Tool	J2377	Proto or Equivalent. Length 19-1/2", Weight 0.27 lbs, Strength 1.5 lbs lbs.	7		
10	Jet Cut Appliflon Sp Handsaw	120150	Stanley or Equivalent. Hardpoint handsaw, unique teeth geometry three cutting edges to cut on forward and reverse strokes, Hardpoint handsaw, unique teeth geometry three cutting edges to cut on forward and reverse strokes, Hard point for long life, Length. 18in, Teeth 7 T.P.I.	10		

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
11	Professional 3/4 hp 8" Industrial Grinder	22018	Craftsman or Equivalent. Designed for heavy-duty grinding, these machines have cast-iron bases and motor housings to dampen vibration. Each features an independently operating lamp, adjustable cast-aluminum tool rests, 120 and 60-grit wheels, wheel dresser, coolant tray, large eye shield, spark arrestors and exhaust ports. Features a 3/4 hp motor that develops 3,450 rpm. Ideal for use on knives, keen-edge tools and finishing and polishing. 8-inch wheels with a 1-inch face. Removable toggle switch. Wt. 95 lbs	4		
12	Heavy-Duty 2" (50mm) Die Grinder	DW888	Dewalt or Equivalent. 5.0 Amp, 19,000 rpm motor provides high power and speed for all 2" grinding applications, AC/DC capacity works off welding machines and generators for increased productivity and versatility, External brush caps for easy servicing, Precision 1/4" collet with 1/8" reducing sleeve for maximum gripping strength - allows user to operate both 1/4" and 1/8" shaft accessories. Includes: 2 wrenches, 1/4" collet, 1/8" reducing sleeve.	4		
13	Mattock Head	5002AE	Spear & jackson or Equivalent. Heat treated carbon steel, For use with pick handle 5020AP, Weight - 3.2KG (7lbs).	5		
14	Multi Purpose Shear	4YP37	Westward or Equivalent Multipurpose Shear, Right/Left Handed, Overall Length (In.) 7-1/2, Length of Cut (In.) 1-5/8, Blade Material Stainless Steel, Blade Edge Straight, Point Type Sharp, Handle Type Straight, Ergonomic, Handle Material PVC Plastic, Handle Color Blue, Safety Latch Locks Blade.	5		

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
15	10" Compact Job Site Table Saw with Rolling Stand	DW744XRS	Dewalt or Equivalent. Exclusive, telescoping fence delivers 24-1/2" rip capacity without sacrificing portability, Rack and pinion design makes fence adjustments fast, smooth and accurate ensuring that the fence is always parallel to the blade, Features a 15.0 Amp high-torque motor with the power to cut pressure-treated lumber and hardwoods, Electronic feedback maintains blade speed during difficult applications, Soft start allows blade to come up to speed without jumping, Telescoping rails retract within the saw top for easy portability, Features a heavy-duty internal motor mechanism which stabilizes the arbor, keeping vibration to a minimum, 2" Dust Collection Port easily connects to a vacuum for efficient dust extraction, 3-1/8" depth of cut at 90° and 2-1/4" at 45°, 26-1/2" X 19-1/4" table surface provides superior material support, Includes: 10" 24-Tooth Carbide Blades, Rolling table saw stand, Miter gauge.	2		
16	6-1/2" Amp Jig Saw	DW331K	All metal gear case and keyless blade lever enhance tool durability in a professional shop environment, Variable strokes per minute delivers optimal cutting speed for all applications, Lever-action keyless blade change makes blade replacement fast and easy, Independently certified to applicable standards.	2		
17	1/2drive Ratchet Speed Handle	5480	Proto or Equivalent. Handles - Sockets & Ratchets Tool Type: Speed Handle Drive Size: 1/2 Overall Length: 18 Finish/Coating: Chrome	2		
18	Timing Gage	CEN 3D487	Central Storm Measuring Tools or Equivalent. 2-Cycle & Small Engine Timing Gage Set No. CEN-3D487 2-Cycle & Small Engine Timing Gage Set 2-Cycle & Small Engine Timing Gage Set Features: 1in. range with .001in. graduations	5		
19	5" Heavy-Duty	D26453K	Dewalt or Equivalent. 3.0 Amp electronic	1		
20	Heavy-Duty 7"/ 9" Si	DW845	Dewalt or Equivalent. Amps 7.0 AC Amps,	2		
21	Replacement Bulb For	INF17-1105	Replacement Infrared Element (bulb) for Infratech Speed Ray 2 Lamp.	4		

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
22	C-Clamp	2HUL8	Westward or Equivalent. Regular Duty, Size 4 In, Throat Depth 3 1/4 In, Min Proof Test 6200 Lb, Load Capacity 6200 Lb, Clamp Type Drop Forged, Spindles Copper Plated, Pad Serrated, Gray, Anvil Grooved, Powder Coat, Ductile Iron Frames, Swivel Pad.	3		
23	3/4 Horsepower 15-Inch Floor Drill Press	15-233	Designed for professional grade use, The DELTA 15-233 3/4 HP 15-inch Floor Drill Press comes with a massive 2-inch diameter quill, extra large spindle bearings, and a spindle pulley that are supported by four oversized, pre-loaded, lubricated-for-life ball bearings for a long, maintenance-free life and maximum pressure at the drill point. This drill press' test-proven speed range provides a true 10-to-1 speed ratio, which means you'll get the exact speed you need for every drilling job on any material--including 450-to-4,700 RPM with a 1,725 RPM motor and 300-to-3,100 RPM with an 1,140 RPM motor. Its efficient variable-speed drive lets you select any spindle speed instantly while the machine is running. A self-locking cam, plus a "snubber" feature hold speed settings constant under all load conditions. Proper belt tension is automatically maintained for full power transmission. A quick and easy belt tension release is provided by the pivoting motor mounting plate, which has a reverse, self-locking taper on the spring-loaded, rubber-tipped plunger that quickly restores correct belt tension. An extra long quill travel provides the extra depth you need for deep hole jobs like skip and gang drilling while also providing the extra stroke required for clearing jigs and fixtures. This press' 3-phase, 3/4 HP motor comes with versatile	1		
24	Work Gloves,	40483	Craftsman or Equivalent. 100% cotton drill work gloves with non-skid dots for easy gripping.	2000		
25	Cowhide Welding A	77548	Hobart or Equivalent. One size fits all. Weight 4 lbs.	50		

**W913FT-11-T--0059
PRICING SPREADSHEET**

ITEM	DESCRIPTION	PART NUMBER	SALIENT CHARACTERISTICS	QTY	UNIT PRICE	TOTAL PRICE
26	Master Lock Warded Keyed Padlock Keyed	22D	Master Lock or Equivalent. Padlock features a durable laminated steel 1-1/2" (38mm) body. Warded locking mechanism minimizes jamming from dirt and grime. Mechanism tolerances make warded locks a frequent choice where sand, ice and other contaminants may jam other types of locks. Steel shackle provides strong cut-resistance. Includes pair of nickel-plated steel keys.	50		
27	Long Sleeve Coverall	Long Sleeve Coverall	Craftsman or Equivalent. Featuring triple needle construction and bar-tack stress points for added toughness, this excellent of work clothes also supplies plenty of pockets, including an oversized utility pocket and a pencil stall on the sleeve, and elastic at the back waist for a snug fit. Non-Stick stain protection built right into the fabric. Front closure with snaps and heavy duty hidden 2-way zipper to keep you regular clothes safe from grime and damage.	337		
28	Landscaper Safety Glasses	90786	AO Safety or Equivalent. Landscaping can pose a daily hazard which requires eye protection to be worn, branches, twigs, dust, and chemicals can all pose a danger to your ocular health. The best thing to do is to take precautions and protect yourself. AO Safety's Landscaper Safety Glasses have been designed in a sporty 180° wraparound style with scratch resistant gray lenses and bright yellow arms. Polycarbonate lenses meet ANSI standard Z87.1 and OSHA requirements as well as ANSI sunglass standard Z80.3 and provide 99.9% UV protection.	502		
29	42" Belt Drive Drum Fan	MVB42B	Marley or Equivalent. Permanently lubricated ODP Motor, 10 ft. grounded 3 conductor cord, Durable 20 gauge steel housing, • Painted steel guards, 8" semi-pneumatic wheels, Double handle design for easy transporting.	10		

TOTAL

0.00