

General Description

Regal® Classic Pearl is a premium quality proprietary acrylic pearl finish with unique properties. Its high-hiding pearl lustre finish provides an elegant look to walls, ceilings, trim, doors, and cabinets. Regal® Classic Pearl is easy-to-use, spatter resistant, fast drying and has no unpleasant odor during application. Its durable satin like finish is ideal for any interior application.

Technical Data

Vehicle Type

Pigment Type

Volume Solids

Coverage per Gallon at Recommended Film Thickness

Recommended Film Thickness – Wet

– Dry

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.

Dry Time @ 77°F – To Touch

(25° C) @ 50% RH – To Recoat

Pastel Base

Proprietary Acrylic Latex

Titanium Dioxide

37.9%

400 – 450 Sq. Ft.

3.8 mils

1.3 mils

1 Hour

1 – 2 Hours

Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.

Dries By

Viscosity

Flash Point

Gloss / Sheen

Surface Temperature at Application – Min.

– Max

Thin With

Clean Up Thinner

Weight Per Gallon

Storage Temperature – Min.

– Max

Evaporation, Coalescence

94 ± 2 KU

None

Pearl

50° F

90° F

See Chart

Clean Water

10.7 lbs

40° F

90° F