

imageRUNNER 5075 (should include all required peripheral accessories and also have the ability to print, scan and fax)

Black & White Copiers



Specifications

Main Unit Specs

Model Name	imageRUNNER 5075
Type	Monochrome Digital Multifunction Imaging System
Imaging System	Laser Dry Electrostatic Transfer
Developing System	Dry Mono Component Toner Projection
Fixing System	Induction Heating Fusing System
Image Server Memory	Standard 1GB RAM + 40GB HDD (Shared)
Max Mailboxes Supported	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes
Max Copy Reservation	20 Jobs
Scanning Resolution	600 x 600 dpi
Printing Resolution	1200 x 1200 dpi (available on certain page description languages)
Interpolated Resolution	1200 x 600 dpi
Halftone	256 Gradations of Grey
Letter	Up to 75 ppm
Letter R	Up to 58 ppm
Legal	Up to 45 ppm
Ledger	Up to 37 ppm
First Copy Time	3.1 Seconds from Platen Glass
Multiple Copies	1 to 9,999
Magnification	100%
Preset Reductions	25%, 50%, 64%, 73%, 78% 121%, 129%, 200%, 400%
Preset Enlargements	Zoom Mode: Platen: 25% - 400% (In 1% Increments) Feeder: 25%-200%(In 1%Increments)
Acceptable Originals	Sheets, books, and 3-Dimensional objects up to 4.4 lb. 11" x 17"
Maximum Original Size	Max. Copy Size: 11" x 17"

Min. Copy Size: 3 7/8" x 5 7/8" (via Stack Bypass)

Standard Paper Capacity	Dual Paper Drawers (1,500 Sheets Each) Dual 550-Sheet Paper Cassettes (550 Sheets Each) 50-Sheet Stack Bypass Optional: 3,500-Sheet Paper Deck
Manual Bypass	50-Sheet Stack Bypass
Maximum Paper Capacity	7,650 Sheets
Output Sizes	
Cassette	Upper: Letter Lower: 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, Free Size (3 7/8" x 5 7/8" to 11 5/8" x 17"), and Envelopes
Bypass	Acceptable Paper Weight: 17 lb. Bond to 110 lb. Index (From All Sources)
Acceptable Paper Weights	
Duplexing	Standard Automatic Trayless Duplexing
Warm Up Time	30 Seconds or less from Main Power Off or Sleep Mode
Exposure Control	Automatic or Manual (9 Levels) 120V AC, 60Hz, 20A Power Consumption: 1.92kW (Max.)
Power Requirements	Plug: NEMA 5-20P
Dimension	47 1/2" x 25 3/8" x 29 1/4" (1,207mm x 643mm x 743mm)
Weight	474 lb. (215 kg)

Accessories

Feeders

Description	Single-Pass Duplex Scan Document Feeder
Acceptable Originals	Statement to 11" x 17"
Scanning Speed	Up to 100 ipm (Letter @ 300 dpi, Two-Sided) Up to 77 ipm (Letter @ 300 dpi, One-Sided)
Capacity	100 Sheets (20 lb. Bond)
Paper Weights	One-Sided Scanning: 11 lb. to 32 lb. Bond Two-Sided Scanning: 13 lb. to 32 lb. Bond

Paper Supply Options

Description	Paper Deck-AD1 (Opt.)
Paper Capacity	3,500 Sheets (20 lb. Bond)
Paper Sizes	Letter
Paper Weights	17 lb. Bond to 110 lb. Index
Dimensions	22 5/8" x 12 3/4" x 23"
Weight	Approx. 65.7 lb.
Description	Paper Deck-AE1 (Opt.)
Paper Capacity	3,500 Sheets (20 lb. Bond)
Paper Sizes	11" x 17", Legal, Letter, Letter-R
Paper Weights	17 lb. Bond to 110 lb. Index

Dimensions 22 5/8" x 23 1/2" x 24 1/2"
Weight Approx. 99.4 lb.

Output Options:

Finishers

Output Trays

Description	Finisher-AD1/Saddle Finisher-AD2 (Opt.)
Paper Weights	17 lb. Bond to 140 lb. Index
Paper Size	11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Free Size (3 7/8" x 5 7/8" to 11 5/8" x 17")
Number Of Trays	3 Trays
Top Tray	Non-Collate Mode (Tray A): 250 Sheets (Letter, Statement-R, Executive) 125 Sheets (11" x 17", Legal, Letter-R)
Middle Tray	Non-Collate Mode (Tray B): 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Collate, Group Modes (Tray B): 1,300 Sheets (Letter, Executive) 650 Sheets (11" x 17", Legal, Letter-R)
Lower Tray	Non-Collate Mode (Tray C): 2,450 Sheets (Letter) 1,700 Sheets (Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Collate, Group Modes (Tray C): 1,700 Sheets (Letter, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Staple Mode (Trays B & C): Tray B, Tray C: 1,300 Sheets/100 Sets [or 7 3/8" (188.4mm) in Height] (Letter, Executive) 650 Sheets/50 Sets [or 3 3/4" (96mm) in Height] (11" x 17", Legal, Letter-R) Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Executive
Staple Capacity	50 Sheets (Letter, Executive) 30 Sheets (11" x 17", Legal, Letter-R)
Staple Positions	Any Corner Staple Double Staple in Right or Left Margin Saddle Stitch (Center Staple)*
Paper Sizes	11" x 17", Legal, Letter-R*
Fold Type	V-folding Saddle-Stitch Tray: Saddle-Stitch Capacity: 15 Sheets (60 Page Booklets) Tray Capacity: 25 Sets (1 to 5 Sheets) 15 Sets (6 to 10 Sheets) 10 Sets (11 to 15 Sheets)*
Dimensions	Finisher-AD1: 44 1/8" x 25 1/2" x 25 7/8" Saddle Finisher-AD2: 44 1/8" x 25 5/8" x 25 7/8"
Weight	Finisher-AD1: Approx. 106 lb. Saddle Finisher-AD2: Approx. 155 lb. Attachable Accessories: Document Insertion Unit-E1, Document Insertion/Folding Unit-F1, Puncher Unit-AT1

Document Inserters

Description	Document Insertion Unit-F1 (Opt. for Fin. AD1/AD)
Paper Weight	Insertion: 17 lb. Bond to 140 lb. Index Folding: 17 lb. - 28 lb. Bond
Paper Sizes	Insertion: 11" x 17", Legal, Letter, Letter-R, Executive C-Fold: Letter-R Z-Fold: 11" x 17", Legal, Letter-R Folding Method: Roller Pressure Folding
Feeder Capacity	100 Sheets C-Fold Output Tray Capacity: 40 Sheets Dimensions (H x W x D): 48 7/8" x 26 1/8" x 26 3/4"

Weight: Approx. 168 lb.

Puncher Unit-AT1 (Option for Finisher-AD1/Saddle Finisher-AD2)

Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R

Acceptable Paper Weight: 17 lb. Bond to 110 lb. Index

Punch Method: Sequential Processing System (1 Sheet at a time)

Punch Type: 2 holes: (Legal, Letter-R)

3 holes: (11" x 17", Letter)

Punch Waste Capacity: Approx. 3,000 Sheets

Dimensions (H x W x D): 32 3/4" x 4 1/4" x 24 1/4"

Weight: Approx. 15.9 lb.

Description	Document Insertion Unit-E1 (Opt.for Fin. AD1/AD)
Paper Weight	17 lb. Bond to 140 lb. Index
Paper Sizes	11" x 17", Legal, Letter, Letter-R, Executive 100 Sheets
Feeder Capacity	Dimensions (H x W x D): 48 7/8" x 26 1/8" x 26 3/4" Weight: Approx. 88.2 lb.
Fax Board	
Description	Super G3 Fax Board-Z2 Public Switched Telephone Network (PSTN) Connection Lines: 1
Applicable Line	Sending/Original Size: Statement to 11" x 17" Receiving/Printing Size: Statement to 11" x 17"
Transmission Speed	ECM-MMR: Approx. 3.2 Seconds/Page G3MR/G3MH: Approx. 13 Seconds/Page JBIG: Approx. 2.6 Seconds/Page Auto Dial Function: Address Book: 1,800 Destinations
Print Board	
Description	UFR II/PCL/PS Printer Kit-R2
Processor	Canon Dual Custom Processors Type: Embedded Print Controller
Standard Memory	1GB (Standard) (Shared)
Hard Disk	40GB (Standard) (Shared)
PDL Support	UFR II, PCL 5e, PCL 6, PS3 Emulation Resolution: PCL 5e/6: 2,400 x 600 dpi (Interpolated) UFR II/PS3 Emulation: 1200 x 1200 dpi
Postscript Fonts	136 Scalable fonts
PCL Fonts	80 Scalable fonts, 10 Bitmap
Interface Connections	10/100Base-TX (RJ-45), USB 2.0 High Speed UFR II: Windows® 2000/XP/Server 2003, Vista, Citrix MetaFrame, Macintosh® OS X (OS 10.2.8 or Later) PCL 5e/6: Windows98/Me/2000/XP/Server 2003, Vista, Citrix MetaFrame PostScript 3: Windows 98/Me/2000/XP/Server 2003, Vista, Citrix MetaFrame Macintosh OS X (OS 10.2.8 or Later) Network Operating Systems: Novell® NetWare® v3.2, 4.1, 4.11, 4.2, 5, 5.1, 6.5 (IPX/SPX) Windows 98/Me/2000/XP/ Server 2003, Vista (TCP/IP) Apple® Macintosh OS 8.0 or Higher (DDP) Solaris™ 1.5x, 2.5x or Later (TCP/IP)
Print Controller Technology	

Send Expansion Sets

Description	Universal Send Kit-F1
Sending Method	Email, I-Fax, File Server (FTP, SMB, IPX, WebDAV), User Inbox, Super G3 Fax (Optional)

Address Book
Capacity

Max. 1,800 Destinations
Max. 5 LDAP Servers

File/E-mail: TIFF, PDF, PDF (OCR), *** Encrypted PDF, #Digital Device Signature PDF,
#Digital User Signature PDF##

File Format

I-Fax: TIFF (MH, MR, MMR)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), NCP (IPX), WebDAV

E-Mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

100 x 100 dpi to 600 x 600 dpi, User Selectable

ENERGY STAR Qualified